


TC1250LS

60Hz POWERED BY CUMMINS SERIES



TECHNICAL SPECIFICATIONS

DIESEL GENERATING SET 208/120V-60Hz-3Phase

Model	TC1250LS	
Power(ESP)	kVA/kW	1090/872
Power(PRP)	kVA/kW	990/792
Starter Voltage	V	24
Rated Current	A	3026
Rated rotation speed	r/min	1800
Power Factor		0.8
Fuel Consumption	L/hour	250.6L / h
Fuel Tank Capacity	L	
Noise level	dB(A)@1m	Silent Type: ≤87

WEIGHT AND DIMENSIONS

GEN-Set	Dimension (L*W*H)	Weight
Open Type	4270mm*2100mm*2480mm	8280kg
Silent Type	12192mm*2438mm*2896mm	15230kg

STANDARDS:

Genset: GB/T2820—2009,ISO8528**Alternator:** LEROY SOMER, TAL A49 D**Diesel Engine:** CUMMINS , KTA38-G4**Standby Power:** Continues running at variable load for duration of an emergency. No overload is permitted on these ratings.**Prime Power:** Continues running at variable load for unlimited periods with 10% overload available for 1 hour in any 12 hour period.

CONFIGURATION:

Standard: Engine, alternator, cooling system, Base frame (excluding fuel tank), shock absorber, air inlet system, control box (including mains floating charge), plastic fan blades (when the engine and water tank do not bring).**Optional:** Base frame (including fuel tank), water jacket heater, fuel water separator, fuel heater, fuel level sensor (only supporting underframe tank), switch box (with switch), power switch, the water level sensor, motor anti condensation heater, automatic fueling system (only supporting base frame including fuel tank), battery frame.**Accessories:** Silencer, bellow, exhaust silencing system accessories (with the matching engine), regular battery, starting cord assembly, data of gen-set, random tool (with the matching engine).

ENGINE Specification

Manufacturer: CUMMINS

Model	KTA38-G4
Engine speed Rated	1800 RPM
Cylinder /Arrangement	12/V
Displacement	38L
Bore and Stroke	159mm×159 mm
Compression ratio	13.9: 1
Max. stand by power at rated RPM	1112KW
Frequency regulation , steady state	± 0.25%
Governor : type	Electrical
Aspiration and Cooling	Turbocharged & Aftercooled

Exhaust System

Exhaust gas flow	3967L/s
Exhaust temperature	524°C
Max back pressure	10kPa

Fuel System

Fuel consumption100% (of the Prime Power)	250.6L / h
Fuel consumption75% (of the Prime Power)	195.2L / h
Fuel consumption50% (of the Prime Power)	139.8L / h
Fuel consumption110% (of the Prime Power)	277.1L / h

Oil system


Total oil capacity w/filters	135.1L
------------------------------	--------

Air intake

Engine air flow	1435L/s
-----------------	---------

Coolant System

Radiator & engine capacity	222.3L
Max water temperature	104°C
Thermostat	82-93°C



Cummins engines with advanced design, reliable performance, durable operation.

Alloy-steel and connecting steel-lever, high durability

High combustion efficiency and low fuel consumption, work continuously

P/T pump injection technology, low cost, completely combustion

Note: All data sheets are for reference only
and subject to change without prior notice.



ALTERNATOR Specification

Manufacturer: LEROY SOMER

Type	TAL A49 D
Number of phase power	3
Factor (Cos Phi)	0.8
Pole	4
Bearing	1
Coupling	Direct
Exciter type	SHUNT
Insulation : class , temperature rise	H / H
Degree of protection	IP23
AVR model	R150
Altitude	≤1000m
Winding Pitch	2/3
Winding Leads	12

FEATURES

- Tight control of procedures right from the initial sales offering through to delivery to the customer, including the design process, manufacturing start-up and production.
- A total quality policy based on making continuous progress in improving operational procedures, involving all departments in the company in order to give customer satisfaction as regards delivery times, conformity and cost.
- Indicators used to monitor process performance.
- Corrective actions and advancements with tools such as FMECA, QFD, MAVP,
- MSP/MSQ and Hoshin type improvement workshops on flows, process re-engineering, plus Lean Manufacturing and Lean Office.
- Annual surveys, opinion polls and regular visits to customers in order to ascertain and detect their expectations.



STANDARDS

IEC 60034, NEMA MG 1.32 - 33, ISO 8528/3, CSA, UL 1446, UL 1004
on request and depending on voltages, marine.

Note: All data sheets are for reference only and subject to change without prior notice.

Control Panel



AUTO START & AUTO MAINS FAILURE CONTROL MODULES

DIMENSIONS

OVERALL

216mm x 158mm x 42mm
(8.5" x 6.2" x 1.6")

PANEL CUTOUT

182mm x 137mm
(7.2" x 5.4")

WEIGHT

400g (0.4kg)



KEY FEATURES

Back-lit icon LCD display
Front panel editing
LED and LCD alarm indication
Power Save mode
CAN and Magnetic Pick-up/Alt.
versions available (specify on ordering)
PC and front panel configuration
4 Digital inputs
3 Analogue inputs
6 Outputs (4 configurable on
Magnetic Pick-up/Alt., 6
configurable on CAN version)
Configurable timers and alarms
Alternative configuration
Event Log (5)
Remote Start input
3 Phase generator monitoring

Current monitoring and protection
Power monitoring(kW, kV A, kV Ar)
3 Phase Mains (Utility) monitoring
(DSE6020 only)
Test button (DSE6020 only)
Battery Voltage monitoring
Engine pre-heat
Hours counter
Comprehensive shutdown or warning
on fault condition

KEY BENEFITS

Automatically transfers between
mains (utility) and generator power
(DSE6020 only)
Hours counter provides accurate
information for monitoring and
maintenance periods
User-friendly set-up and button

Multiple engine parameters are
monitored simultaneously
Module can be configured to suit
individual applications
Compatible with a wide range of
CAN engines
Uses DSE Configuration Suite PC
software for simplified
configuration
IP65 rating (with optional gasket)
offers increased resistance to water
ingress
Licence-free PC software.



Una compañía de servicio a su servicio

gerencia@fcpowersolutions.com.co / 310 834 9075 / Carrera 48 # 166-66, oficinas 105 C
Bogotá-Colombia // www.fcpowersolutions.com.co